

# TP12™

active pa

## CHARACTERISTICS

- Two-way active PA system
- TWS connection
- Bass Reflex
- Digital display
- Signal and clipping indicator LEDs
- Ø 35 mm stand anchorage
- XLR full range derivation
- Mic/Line input selector (inputs 1 and 2)
- Independent input volume controls
- Independent treble and bass equalization controls
- Connections: Bluetooth; XLR/TRS (x2); RCA; AUX 3,5 mm
- DSP with 4 preset equalizations
- Voltage selector 110/220 V
- Buttons: mode, vol +/-, previous, next, play/pause for navigation and control
- Includes power cable



# TP12™

active pa

## SPECIFICATIONS

- Color: Black
- Bluetooth range: 10 m
- Bluetooth version: 5.0
- Bluetooth Audio Codec: SBC
- Frequency response: 20 – 20k Hz
- Power output: 300 W RMS
- Distortion < 0,5%
- Signal-noise ratio (S/R) > 90 dB
- Drivers:
  - High: 1,35" (x1); 8 Ω; Titanium
  - Low: 12" (x1); 4 Ω; magnetic isolation
- Product size: 357 x 352 x 612 mm
- Materials: iron mesh / PP plastic box
- Connectivity: Bluetooth; RCA/TRS (x2); XLR
- Power cable length: 1,5 m

## LOGISTICS

- Gift Box/Master Carton: 430 x 400 x 680 mm; 20 kg
- EAN: 4260411273271
- DUN: 14260411273278
- HK: HK096-03670

